


STATEMENT OF LINE





(Linear, L- and U-shaped)

Brackets




Sleeve Bracket




Top Mounted Bracket



Top Mounted Bracket with optional Clamp



Fixed Privacy Modesty Bracket



Height Adjustable Bracket



Corner Connector



FINISHES

Screens Briquette Shadow Ash Pearl Celestial Verde **Brackets** Tuscan Platinum Saffron White Sand Black Seafoam

Screens



Briquette FC1



Verde FC6



Shadow



Tuscan FC7



Ash FC3



Saffron FC8



Pearl FC4



Sand FC9



Celestial



Seafoam FC10

Brackets



Platinum



White F2



Black F3

SPECIFICATIONS

Standard Widths	23", 28", 44", 46", 50", 52", 56", 58", 62", 64", 68", 70"
Standard Heights	18", 23" and 28"
Thickness	.7"
Applications	Linear, L-Shape and U-Shape
Mounting Options	3F Worksurface Brackets, ILINE Clips or KINEX Clips
Density	3kg/m2
Composition	100% Polyester (min. 50% recycled PET fiber)
Sound Absorption	NRC Value .85
Environmental	Oeko-Tex Standard 100 certified, VOC free
Recyclability	100% Recyclable
Bracket Compliance	BIFMA X5.6-2016

INSTALLATION TIME

10 minutes per workstation, including brackets.

WARRANTY

10 years

CERTIFICATIONS

Oeko-Tex Standard 100 BIFMA X5.6-2016 Indoor Advantage Gold™

CARE & MAINTENANCE INSTRUCTIONS

Wipe with a damp cloth using water or gentle, nonabrasive cleaner. For guaranteed safety, patch test with diluted cleaner before wiping entire surface. Wipe dry with a clean cloth.

DISINFECTING

Disinfect using a ratio of 5 tablespoons (1/3 cup) bleach per gallon of water OR 4 teaspoons bleach per quart of water. This solution ratio is consistent with CDC instruction for virus and bacteria control. Do not soak or rub the diluted bleach solution into the 3F material. Instead, spray apply the diluted bleach solution as a mist and let sit for at least 1 minute before wiping off any cleaning solution residue with a damp cloth. For guaranteed safety, patch test diluted bleach solution in an inconspicuous place on the product before applying widely.



FEATURES



Supports Linear, L- and U-shapes



10 Verve color options



Tackable and sound-absorbing

MOUNTING BRACKETS



Top Mounted



Top Mounted with Clamp



Sleeve



Fixed Privacy Modesty



User Height Adjustable



ILINE or KINEX clips



Screen Corner Connector

